Installation Instructions for GS-W2

1. Locate the filter below the refrigerator. Remove the filter by rotating it ¼ turn counter-clockwise. Remove the knob from the old filter.

2. Remove sanitary cap from new filter.

3. Place the knob from the old filter onto the new filter. Insert the filter into refrigerator and turn it ¼ turn clockwise until the filter is firmly seated.



4. Run approximately 2.5 gallons of water from the dispenser periodically to clear the system and to receive a good flow. If the water flow is slower than usual, please repeat step 3.

   Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.

5. Check the filter for any noticable leaks. If leaks are detected, please repeat.

6. To reset the filter monitor light, please refer to your refrigerator owner's manual for specific instructions.

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Min Operating Pressure:	30 psi (207 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Life:	6 months or 300 gallons (1,136 liters)

This GS-W2 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.

Installation shall comply with applicable state and local regulations

Manufactured by: Aquamor, LLC, Temecula, CA

For further questions or assistance, please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiolocally unsafe or of unkown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR. The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.

P/N 803194-r1

Instrucciones de instalación para GS-W2

1. Localiza el filtro por debajo de la nevera. Retire el filtro girándolo un cuarto de vuelta en dirección contra las agujas del reloj. Retire la perilla del filtro viejo.

2. Retire la tapa sanitaria del filtro nuevo.

3. Coloque la perilla del filtro viejo al nuevo filtro. Coloca el filtro en el refrigerador y girarlo un cuarto de vuelta hacia la derecha hasta que el filtro esté firmemente asentado.

4. Descarga aproximadamente 2,5 litros de agua del dispensador periódicamente para aclarar el sistema y para recibir un buen flujo. Si el flujo de agua es más lenta de lo habitual, por favor, repita paso 3.

   Nota: Flujo inicial puede ser más lenta de lo esperado. Flujo total se debe restaurar dentro de 24-36 horas

5. Inspecciona el filtro de flujas. Si se detectan fugas, por favor, repita paso 3.

6. Para restablecer la luz de control del filtro, consulte el manual del propietario de su refrigerador para obtener instrucciones específicas.

Tasa de Flujo:	.5 gpm (1.89 lpm)
Temperatura de Funcionamiento:	33°-100°F (0.6°-38°C)
Presión Mínima de Funcionamiento:	30 psi (207 kPa)
Presión Máxima de Funcionamiento:	100 psi (689 kPa)
Vida Útil:	6 months or 300 gallons (1,136 liters)

Este GS-W2 es probado y certificado por NSF International NSF / ANSI 42 para la reducción de cloro, sabor y olor.

La instalación debe cumplir con las regulaciones estatales y locales aplicables.

Fabricado por: Aquamor, LLC Temecula, CA

Para preguntas o ayuda, por favor llame (866) 218-8473.

Advertencia: Para reducir el riesgo de daños materiales debido a fugas de agua, el tapón de derivación del filtro debe ser utilizado cuando un cartucho de recambio filtro no está instalado. Sólo para aplicaciones de agua fría. No use con agua que no sea microbiológicamente insegura o de calidad desconocida sin una desinfección adecuada antes o después del sistema. Proteja contra la congelación. CAMBIAR FILTRO CADA 6 MESES, O SI MAL GUSTO O OLOR ocurrir. El riesgo asociado con las piezas pequeñas puede causar asfixia si se ingieren. Mantenga a los niños lejos de las piezas durante la sustitución del filtro de agua.

P/N 803194-r1